

1

- LEGEND**

 - Federal Navigation Channel ○○○ Cable Area
 - Federal Navigation Center Line ■ Placement A
 - As-built Pipeline/Cable [] Anchorage A
 - Unconfirmed Pipeline/Cable ✗ Obstruction
 - Project Depth Contour ↗ Wrecks-Sub


- The legend includes the following entries:

 - Borrow Area: A blue square marker.
 - Shoalest Sounding**: A yellow circle marker.
 - Beacon, General: A black star with a white center marker.
 - Red Navigation Buoy: A red diamond marker.
 - Green Navigation Buoy: A green diamond marker.

Depth Ranges (from top to bottom):

 - 0' and above (green)
 - 0' to -5' (light yellow)
 - 5' to -10' (orange)
 - 10' to -20' (light blue)
 - 20' to -30' (medium blue)
 - 30' to -35' (purple)
 - 35' to -40' (dark blue)
 - 40' to 45' (pink)
 - 45' and below (white)

	LWRP:	2.6
	Gage Reading:	BR: 32.07 NAVD88
	Sea Conditions:	CALM
	Vessel Name:	OB-169
	Survey Type:	CS
	Sounding Frequency***:	200



1000

0 500 1,000 1,500 2,000 2,500

NOTES:

Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane
Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet

Vertical Datum:
Soundings are shown in feet and indicate depths below Low Water Reference Plane 2007 (NAVD).

The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE crew

202115 Aerial Photography data source: NAIP, USDA-FSA

Reference is N.O.A.A. Navigation Chart No. 11370.

** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

**Sheet
Reference
Number**

Revision Number:
5.25.04.03-5.25.04.03