



** Shoalest Sounding per Quarter per Reach.

*** High frequency (20 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.



DISTRIBUTION STATEMENT: The data represents the results of data collection/processing by a specific US Army Corps of Engineers activity and includes the general existing conditions. As such, the data is not necessarily suitable for other uses without further research and/or analysis. The United States shall be responsible for the results of its application of the data for other than its intended purpose.

Data Constraints: Hydrographic data is subject to change rapidly due to several factors including but not limited to dredging activity and natural shoaling and scouring processes. The U.S. Army Corps of Engineers does not guarantee the accuracy of the hydrographic conditions when developing the data. The information depicted on this map represents the results of a survey conducted on the date indicated and can only be considered to represent the general condition existing at that time. The information depicted on this map represents the results of a survey conducted on the date indicated and can only be considered to represent the general condition existing at that time.

MISSISSIPPI RIVER - B.R. TO GULF REDEYE CROSSING MD_04_RED_20220503_CS
03 May 2022

Sheet Reference Number
4 of 97

Revision Number:
4-200420