


**DISCLAIMER:** The data represents the results of data collection for a specific US Army Corps of Engineers project. It is only valid for its intended use, control, time and accuracy specifications. The user is responsible for the results. The application of the data for other than its intended purpose is not recommended. Hydrographic survey data is subject to change due to several factors including but not limited to dredging, sedimentation, and changes in bathymetry. The US Army Corps of Engineers does not assume responsibility for changes in the hydrographical conditions when developed after the date of the survey. Product maintainers should not rely solely upon it.

Submitted:	Checked By:	Checked By:
Recommended:	Checked By:	Checked By:
Approved:	Checked By:	Checked By:

**MISSISSIPPI RIVER - B. R. TO GULF**  
**MEDORA CROSSING**  
**MD\_08\_MED\_20210623\_CS**  
**23 June 2021**



LEGEND		DIKE ELEVATION	
--- Federal Navigation Channel	● Cable Area	0' and above	1 -10 NGVD
— Federal Navigation Center Line	□ Placement Area	0' to -5'	OR -12.1 LWRP
— As-built Pipeline/Cable	□ Anchorage Area	-5' to -10'	2 -4 NGVD
..... Unconfirmed Pipeline/Cable	⊗ Obstruction Point	-10' to -20'	OR -8.1 LWRP
— Project Depth Contour	⚓ Wrecks-Submerged	-20' to -30'	3 -2 NGVD
	★ Beacon, General	-30' to -35'	OR -0.1 LWRP
	◆ Red Navigation Buoy	-35' to -40'	
	◆ Green Navigation Buoy	-40' to -45'	
		-45' and below	

**NOTES:**

Horizontal Coordinate System:  
 North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:  
 Soundings are shown in feet and indicate depths below Low Water Reference Plane 2007 (NAVD).  
 Distances on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE crew.  
 2015 Aerial Photography data source: NAIP, USDA-FSA-APFO Aerial Photography Field Office.

Reference is N.O.A. Navigation Chart No. 11370.

\*\* Shoalest Sounding per Quarter per Reach.

\*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

LWRP: 2.1  
 Gage Reading: BR:27.2 D:17.8 USED:24.4 NAVD  
 Sea Conditions: CALM  
 Vessel Name: M/V LAFOURCHE  
 Survey Type: CS  
 Sounding Frequency\*\*\*: HIGH

Scale: 0 500 1,000 1,500 2,000 2,500 Feet

**Sheet Reference Number**  
**8 of 97**