




Distribution liability: The data represents the results of data collection and processing by a specific US Army Corps of Engineers activity and relates to the general existing conditions. As such, the user accepts the data "as is" without any guarantee or warranty. The user is responsible for the results of any application of the data for other than its intended purpose. Hydrographic survey data is subject to change rapidly due to several factors including but not limited to dredging operations, changes in water levels, and scouring processes. The user is responsible for keeping the data current. The data is provided for informational purposes. This data is intended for U.S. Army Corps of Engineers personnel and contractors only. It is not to be distributed outside the Corps of Engineers without prior approval.

U.S. ARMY CORPS OF ENGINEERS	
NEW ORLEANS DISTRICT	
Surveyed By:	RYLAND SIMMONS
Submitted:	
Recommended:	Chief Survey Section
Approved:	Chief Waterway Maintenance Section

MISSISSIPPI RIVER - B.R. TO GULF
GRANADA CROSSING
MD_10_GRA_20240207_CS
07 February 2024



NOTES:

Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum: Soundings are shown in feet and indicate depths below Low Water Reference Plane 2007 (NAVD). Distances on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE crew. 2015 Aerial Photography data source: NAIP, USDA-FSA-APFO Aerial Photography Field Office. Reference is N.O.A.A. Navigation Chart No. 11370.

** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

Sheet
Reference
Number
10 of 97

Revision Number:
4.2-200420