



LEG

- |       |                                |    |                   |   |                       |
|-------|--------------------------------|----|-------------------|---|-----------------------|
| ---   | Federal Navigation Channel     | ○○ | Cable Area        |   | Borrow Area           |
| —     | Federal Navigation Center Line | □  | Placement Area    | ● | Shoalest Sounding**   |
| —     | As-built Pipeline/Cable        | □□ | Anchorage Area    | ★ | Beacon, General       |
| ..... | Unconfirmed Pipeline/Cable     | ⊗  | Obstruction Point | ◆ | Red Navigation Buoy   |
| —     | Project Depth Contour          | ↗  | Wrecks-Submerged  | ◆ | Green Navigation Buoy |

  
LWRP: 1.7  
Gage Reading: BR:39.1 D:28.2 USED:31.3 NAVD  
Sea Conditions: CALM  
Vessel Name: M/V LAFOURCHE  
Survey Type: CONDITION  
Sounding Frequency\*\*\*: HIGH

ES:

ntal Coordinate System:  
American Datum of 1983 (NAD83), projected to the State Plane  
Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

l Datum:  
ings are shown in feet and indicate depths below Low Water Reference Plane 2007 (NAVD).  
ces on the Mississippi River, above and below Head of Passes are shown  
in parentheses.

Location of navigation aids are base on and provided by the U.S. Coast Guard and USACE crew.

Aerial Photography data source: NAIP, USDA-FSA-AP

h frequency (200 kHz) survey data represents the first signal return at a sounding  
n and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz)  
data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom  
al. Low frequency accuracies may vary depending on channel conditions and fathometer  
s.

## Sheet Reference Number

Revision Number:  
4.0-201907022