



\*\* Shoalest Sounding per Quarter per Reach.  
\*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

Sheet  
Reference  
Number  
30 of 97

Revision Number:  
4.1-20191105

US Army Corps of Engineers  
District: CEMVN

Distribution Notice: The data represents the results of data collection/processing for a specific US Army Corps of Engineers activity and includes the general existing conditions. As such, the United States Government makes no warranties, express or implied, regarding the accuracy of the data or its suitability for any particular purpose. The United States shall not be liable for damages resulting from the use of the data for other than its intended purposes.  
Data Constraints: Hydrographic survey data is subject to change due to several factors including but not limited to dredging activities and natural shoals and scouring processes. The U.S. Army Corps of Engineers shall not be liable for damages resulting from the use of the hydrographic conditions which develop after the date of publication. This data is intended for U.S. Army Corps of Engineers internal use. Please contact the U.S. Army Corps of Engineers for further information.

<b>U.S. ARMY CORPS OF ENGINEERS</b>	
NEW ORLEANS DISTRICT	
Surveyed By:	DSIH
Submitted:	
Recommended:	One I Survey Section
Approved:	One I Waterways Maintenance Section
Checked By:	AO

**MISSISSIPPI RIVER - B.R. TO GULF**  
**BELMONT CROSSING**  
**MD\_30\_BEI\_X\_20200716\_AD**  
16 July 2020