



The logo consists of a red square containing a white stylized castle or fort icon with three towers and a central archway. A registered trademark symbol (®) is located at the bottom right corner of the square.

The United States Government furnishes the recipient accepts and uses them with the express understanding that the US Government makes no warranties, concerning the accuracy, completeness, suitability for any particular purpose of the data furnished. The United States shall be liable to any person by reason of any use of data belonging to the Government. Therefore the recipient may not transfer the data to anyone as other than documented data. The recipient may not transfer without also transferring this Disclaimer.

Distribution Liability: The data represents the results of data collection/processing for a specific US Army Corps of Engineers activity and indicates the general existing conditions. As such, it is only valid for its intended use, content, time and accuracy specifications. The user is responsible for the results of any of the application of the data for other than its intended purpose.

Data Constraints: Hydrographic survey data is subject to change rapidly due to several factors including but not limited to dredging activity and natural shoaling and scouring processes. The U. S. Army Corps of Engineers accepts no responsibility for changes in the hydrographic conditions which develop after the date of publication. This data is intended for U. S. Army Corps of Engineers

<p>C. A. NEW ORLEANS DISTRICT NEW ORLEANS DISTRICT</p>	<p>Surveyed By: DJS/SR _____</p>	<p>Plotted By: BD _____</p>	<p>Checked By: AO _____</p>
<p>Submitted: _____</p>	<p>Recommended: Chief, Survey Section _____</p>	<p>Approved: _____</p>	

**MISSISSIPPI RIVER - B.R. TO GULF
BELMONT CROSSING
MD_30_BEL_20190905_CS
05 September 2019**

ES:

ntal Coordinate System:
American Datum of 1983 (NAD83), projected to the State Plane
nate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

l Datum:
ings are shown in feet and indicate depths below Low Water Reference Plane 2007 (NAVD).

ces on the Mississippi River, above and below Head of Passes are shown
le intervals.

cation of navigation aids are base on and provided by the U.S. Coast Guard and USACE crew.

erial Photography data source: NAIP, USDA-FSA-APFO Aerial Photography Field Office.

ence is N.O.A.A. Navigation Chart No. 11370.

allest Sounding per Quarter per Reach.

h frequency (200 kHz) survey data represents the first signal return at a sounding
n and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz)
data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom
al. Low frequency accuracies may vary depending on channel conditions and fathometer
s.

LWRP: 1.2
 Gage Reading: D:11.0 R:8.2 USED:9.4 NAVD
 Sea Conditions: CALM
 Vessel Name: OB-189
 Survey Type: CONDITION
 Sounding Frequency***: HIGH

Feet

0 500 1,000 1,500 2,000 2,500

LEGEND

--- Federal Navigation Channel	○ ○ Cable Area	□ Borrow Area	0' and above
— Federal Navigation Center Line	□ Placement Area	● Shoalest Sounding**	0' to -5'
— As-built Pipeline/Cable	[] Anchorage Area	★ Beacon, General	-5' to -10'
..... Unconfirmed Pipeline/Cable	⊗ Obstruction Point	◆ Red Navigation Buoy	-10' to -20'
— Project Depth Contour	✗ Wrecks-Submerged	◆ Green Navigation Buoy	-20' to -30'
			-30' to -35'
			-35' to -40'
			-40' to 45'
			-45' and below

