U.S. ARMY CORPS OF ENGINEERS 3,859,000 3,856,000 320,000 3,862,000 3,865,000 317,000 3,868,000 of Engineers District: CEMVN LIGHTED 52 GREEN BUOY 52 MISSISSIPPI RIVER - B.R. BURAS - SHEET 2

MD_92_BU2X_2023072 _BU2X_202307 20 July 2023 3,853,000 3,859,000 314,000 3,856,000 311,000 3,862,000 3,865,000 VICINITY MAP NOTES: Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Myrtle Grove **LEGEND** 0' and above LWRP: Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. EMPIRE VRN: 1.8 NAVD AVG. 0' to -5' Gage Reading: --- Federal Navigation Channel Cable Area Shoaling Area Point A La Hache CALM Sea Conditions: -5' to -10' Soundings are shown in feet and indicate depths below Low Water Reference Plane 2007 (NAVD). Vessel Name: OB-167 -10' to -20' — Federal Navigation Center Line Placement Area Shoalest Sounding** Distances on the Mississippi River, above and below Head of Passes are shown CONDITION Survey Type: -20' to -30' at 1 mile intervals. As-built Pipeline/Cable Anchorage Area Beacon, General Sounding Frequency***: -30' to -35' The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE crew. -35' to -40' ∅ Obstruction Point Unconfirmed Pipeline/Cable Red Navigation Buoy 2017 Aerial Photography data source: NAIP, USDA-FSA-APFO Aerial Photography Field Office. -40' to 45' Sheet Port Sulphur Wrecks-Submerged — Project Depth Contour -45' to 50' Reference is N.O.A.A. Navigation Chart No. 11370. Reference Green Navigation Buoy 1,000 1,500 2,000 500 -50' and below Number ** Shoalest Sounding per Quarter per Reach. 92 **of** 97 *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz)

Esri, HERE, Garmin, (c) Open StreetMap the GIS user community

survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom

Revison Number: 4.2-20200420

material. Low frequency accuracies may vary depending on channel conditions and fathometer