U.S. ARMY CORPS OF ENGINEERS 2,773,000 464,000 2,770,000 **US Army Corps** of Engineers District: CEMVN MERMENTAU RIVER
LOWER RIVER

38_LWR_20190305_CS_
05 March 2019 2,773,000 2,770,000 NOTES: VICINITY MAP Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. **LEGEND** Gage Reading: 2.5 MLG AVG Sea Conditions: CALM --- Federal Navigation Channel Cable Area Borrow Area Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). M/V OB189 Vessel Name: — Federal Navigation Center Line Placement Area The location of navigation aids are base on and provided by the U.S. Coast Guard. Shoalest Sounding** Survey Type: CONDITION -15' and above 2015 Aerial Photography data source: NAIP. 1998 DOQQ imagery shown in green from USGS. Sounding Frequency***: HIGH Anchorage Area As-built Pipeline/Cable Beacon, General ____ -15' and below ∅ Obstruction Point Reference is N.O.A.A. Navigation Chart No. 11344 and 11348. Unconfirmed Pipeline/Cable Red Navigation Buoy Feet Sheet ** Shoalest Sounding per Quarter per Reach. Wrecks-Submerged — Project Depth Contour Reference **Green Navigation Buoy** *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) 500 1,000 Number survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer 8 **of** 25 Esri, HERE, Garmin, © OpenStreetMap contributors, and the GIS user community Revison Number: 3.12-20160811