U.S. ARMY CORPS OF ENGINEERS 2,773,000 464,000 2,770,000 US Army Corps of Engineers District: CEMVN MERMENTAU RIVER
LOWER RIVER
M_08_LWR_20230323_C
23 March 2023 2,773,000 2,770,000 NOTES: **VICINITY MAP** Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. **LEGEND** NTRIP VRS RTK: 3.78 MLG AVG. Gage Reading: CALM Sea Conditions: --- Federal Navigation Channel Cable Area Borrow Area Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). OB-169 Vessel Name: — Federal Navigation Center Line Placement Area The location of navigation aids are base on and provided by the U.S. Coast Guard. Shoalest Sounding** CONDITION Survey Type: -15' and above 2017 Aerial Photography data source: NAIP. 1998 DOQQ imagery shown in green from USGS. Sounding Frequency***: LOW As-built Pipeline/Cable Anchorage Area Beacon, General ____ -15' and below ∅ Obstruction Point Reference is N.O.A.A. Navigation Chart No. 11344 and 11348. Unconfirmed Pipeline/Cable Red Navigation Buoy Feet Sheet ** Shoalest Sounding per Quarter per Reach. — Project Depth Contour Wrecks-Submerged Reference **Green Navigation Buoy** *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) 500 1,000 Number survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer 8 **of** 25 Esri, HERE, Garmin, (c) OpenStreetMap contributors, and the GIS user community Revison Number: 4.2-20200420