U.S. ARMY CORPS OF ENGINEERS 2,788,000 2,785,000 2,782,000 Legend **US Army Corps** of Engineers District: CEMVN MERMENTAU RIVER LOWER RIVER 10_LWR_20231109_CS_ 09 November 2,785,000 2,782,000 470,000 NOTES: **VICINITY MAP** Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. **LEGEND** CP/GC:3.0 MLG AVG Gage Reading: CHOP, WINDY --- Federal Navigation Channel Cable Area Borrow Area Sea Conditions: Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). OB184 Vessel Name: The location of navigation aids are base on and provided by the U.S. Coast Guard. Shoalest Sounding** CONDITION, SB Survey Type: -15' and above 2017 Aerial Photography data source: NAIP. 1998 DOQQ imagery shown in green from USGS. Sounding Frequency***: HIGH As-built Pipeline/Cable Anchorage Area Beacon, General ____ -15' and below ∅ Obstruction Point Reference is N.O.A.A. Navigation Chart No. 11344 and 11348. ---- Unconfirmed Pipeline/Cable Red Navigation Buoy Feet Sheet ** Shoalest Sounding per Quarter per Reach. — Project Depth Contour Wrecks-Submerged Reference **Green Navigation Buoy** *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) 500 1,000 Number survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer 10 **of** 25 Esri, HERE, Garmin, (c) OpenStreetMap contributors, and the GIS user community Revison Number: 4.2-20200420