



LE

- | | | <u>Legend</u> | |
|-------|--------------------------------|---------------|-------------------|
| --- | Federal Navigation Channel | ○ ○ | Cable Area |
| — | Federal Navigation Center Line | □ | Placement Area |
| — | As-built Pipeline/Cable | □□ | Anchorage Area |
| | Unconfirmed Pipeline/Cable | ⊗ | Obstruction Point |
| — | Project Depth Contour | ↗ | Wrecks-Submerged |
| | | ■ | Borrow |
| | | ● | Shoales |
| | | ★ | Beacon, |
| | | ◆ | Red Nav |
| | | ◆ | Green N |

- A vertical color scale representing water depth ranges. The scale transitions through several colors: bright green for depths of 0' and above, yellow for 0' to -5', orange for -5' to -10', light blue for -10' to -20', medium blue for -20' to -30', purple for -30' to -35', dark blue for -35' to -40', magenta for -40' to 45', and grey for depths of -45' and below.

Color	Depth Range
bright green	0' and above
yellow	0' to -5'
orange	-5' to -10'
light blue	-10' to -20'
medium blue	-20' to -30'
purple	-30' to -35'
dark blue	-35' to -40'
magenta	-40' to 45'
grey	-45' and below

LWRP: 2.8
 Gage Reading: BR:12.7 D:
 Sea Conditions: CALM
 Vessel Name: M/V OB189
 Survey Type: CONDITION
 Sounding Frequency***: HIGH

Feet

0 500 1,000 1,500 2,000 2,500

NOTES

Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane
Coordinate System, UTM Zone 13N, NAD83

Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.
Vertical Datum:
Soundings are shown in feet and indicate depths below Low Water Reference Plane 2007 (NGVD).
Distances on the Mississippi River, above and below Head of Passes are shown
in miles and kilometers.

The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE crew.

2010 Aerial Photography data source: NAIP, USDA-FSA

** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

Sheet Reference Number