



L

- | | | <u>LINE</u> | |
|-------|--------------------------------|-------------|-----------------------|
| --- | Federal Navigation Channel | ○ ○ | Cable Area |
| — | Federal Navigation Center Line | □ | Placement Area |
| — | As-built Pipeline/Cable | □□ | Anchorage Area |
| | Unconfirmed Pipeline/Cable | ⊗ | Obstruction Point |
| — | Project Depth Contour | ↗ | Wrecks-Submerged |
| | | □ | Borrow Area |
| | | ● | Shoalest Sounding** |
| | | ★ | Beacon, General |
| | | ◆ | Red Navigation Buoy |
| | | ◆ | Green Navigation Buoy |

LWRP: 2.8
Gage Reading: BR:19.7 D:12.2 USED:19.9 NGVD
Sea Conditions: CALM
Vessel Name: M/V LAFOURCHE
Survey Type: CONDITION
Sounding Frequency***: HIGH

18

ntal Coordinate System:
American Datum of 1983 (NAD83), projected to the State Plane
Coordinate System (NAD83) (ft)

l Datum:
ings are shown in feet and indicate depths below Low Water Reference Plane 2007 (NGVD).
ces on the Mississippi River, above and below Head of Passes are shown

Location of navigation aids are base on and provided by the U.S. Coast Guard and USACE crew.

This is NGA Navigation Chart No. 11370.

h frequency (200 kHz) survey data represents the first signal return at a sounding
n and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz)
data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom
al. Low frequency accuracies may vary depending on channel conditions and fathometer
s.

Sheet Reference Number

Revision Number:
3.12-20160811