



LE

- SOURCE**

— Federal Navigation Channel	○ ○	Cable Area	□	Borrow Area	0' and above
— Federal Navigation Center Line	□	Placement Area	●	Shoalest Sounding**	0' to -5'
— As-built Pipeline/Cable	[]	Anchorage Area	★	Beacon, General	-5' to -10'
..... Unconfirmed Pipeline/Cable	⊗	Obstruction Point	◆	Red Navigation Buoy	-10' to -20'
— Project Depth Contour	★	Wrecks-Submerged	◆	Green Navigation Buoy	-20' to -30'
					-30' to -35'
					-35' to -40'
					-40' to 45'
					-45' and below

A compass rose with cardinal directions (N, S, E, W) and a scale bar labeled "Feet".

LWRP: 2.8
 Gage Reading: BR:18
 Sea Conditions: CALM
 Vessel Name: OB-18
 Survey Type: COND
 Sounding Frequency***: HIGH

0 500 1,000 1,500 2,000 2,500

NOTES:

Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane
Alaska FIPS 102L Transverse Mercator, NAD83

Vertical Datum:
Elevations are shown in feet and indicate depths below Low Water Reference Plane 2007 (NGVD).
Distances on the Mississippi River, above and below Head of Passes are shown.

The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE crew.

15 Aerial Photography data source: NAIP, USDA-FSA-APFO Aerial Photography Field Office.

ference is N.O.A.A. Navigation Chart No. 11370.

High frequency (200 kHz) survey data represents the first signal return at a sounding station and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

Sheet Reference Number