

LE

- LINE**

 - Federal Navigation Channel
 - Federal Navigation Center Line
 - As-built Pipeline/Cable
 - Unconfirmed Pipeline/Cable
 - Project Depth Contour


SOUNDING

 - ○ Cable Area
 - Placement Area
 - [] Anchorage Area
 - ⊗ Obstruction Point
 - ↗ Wrecks-Submerged

BUOYS

 - Borrow Area
 - Shoalest Sounding**
 - ★ Beacon, General
 - ◆ Red Navigation Buoy
 - ◆ Green Navigation Buoy

	0' and above
	0' to -5'
	-5' to -10'
	-10' to -20'
	-20' to -30'
	-30' to -35'
	-35' to -40'
	-40' to 45'
	-45' and below



W

Feet

0 500 1,000 1,500 2,000 2,500

NOTES:

Coordinate System:
Datum of 1983 (NAD83), projected to the State Plane
100' FLS Vertical Datum, North American Datum of 1983

shown in feet and indicate depths below Low Water Reference Plane 2007 (NGVD).
Mississippi River, above and below Head of Passes are shown

navigation aids are base on and provided by the U.S. Coast Guard and USACE crew.

topography data source: NAIP, USDA

ding per Quarter per Reach.

frequency (200 kHz) survey data represents the first signal return at a sounding and include suspended solids, known as "fluff", if present. Low frequency (20 kHz) usually penetrates through this "fluff" layer to depict elevations of consolidated bottom frequency accuracies may vary depending on channel conditions and fathometer

Sheet Reference Number