



<u>LEGEND</u>	
— Federal Navigation Channel	○ Cable Area
— Federal Navigation Center Line	■ Placement Area
— As-built Pipeline/Cable	□ Anchorage Area
..... Unconfirmed Pipeline/Cable	★ Beacon, General
— Project Depth Contour	✖ Obstruction Point
	◆ Red Navigation Buoy
	◆ Green Navigation Buoy
	➤ Wrecks-Submerged

LWRP: 2.4  
Gage Reading: BR:19.6 D:12.35 USED:18.40 NGVD  
Sea Conditions: CALM  
Vessel Name: VESSEL\_NAME  
Survey Type: CONDITION  
Sounding Frequency\*\*\*: HIGH

0' and above  
0' to -5'  
-5' to -10'  
-10' to -20'  
-20' to -30'  
-30' to -35'  
-35' to -40'  
-40' to -45'  
-45' and below

W N E S  
Feet  
0 500 1,000 1,500 2,000 2,500

**NOTES:**  
Horizontal Coordinate System:  
North American Datum of 1983 (NAD83), projected to the State Plane  
Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:  
Soundings are shown in feet and indicate depths below Low Water Reference Plane 2007 (NGVD).  
Distances on the Mississippi River, above and below Head of Passes are shown  
at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE crew.  
2010 Aerial Photography data source: NAIP, USDA-FSA-APFO Aerial Photography Field Office.  
Reference is N.O.A.A. Navigation Chart No. 11370.

\*\* Shoal sounding per Quarter per Reach.

\*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding  
location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz)  
survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom  
material. Low frequency accuracies may vary depending on channel conditions and fathometer  
settings.



Distribution Label: The data represents the results of data collection/processing for a specific US Army Corps of Engineers activity and indicates the general existing conditions. Such descriptions are not necessarily intended for the results of any specific survey or investigation. The user is responsible for the results of any application of the data for other than its intended purpose.  
Data Constraints: Hydrographic survey data is subject to change rapidly due to severe events including but not limited to dredging activities and natural shoaling and scouring processes. The U.S. Army Corps of Engineers and the National Oceanic and Atmospheric Administration do not warrant the data to be suitable for hydrographic purposes. The data is intended for U.S. Army Corps of Engineers use only.  
Disclaimer: This data is intended for U.S. Army Corps of Engineers use only. The data is furnished without warranty. The U.S. Army Corps of Engineers and the National Oceanic and Atmospheric Administration disclaim all liability for damages resulting from the use of this data.

U.S. ARMY CORPS OF ENGINEERS NEW ORLEANS DISTRICT	
Surveyed By:	RYLAND/SONNIER
Submitted:	
Project By:	BD
Checked By:	AO
Approved:	One I. Waterways Maintenance Section
Approved:	One I. Waterways Maintenance Section

**MISSISSIPPI RIVER - B.R. TO GULF**  
**SARDINE POINT RECON**  
**MR\_06\_SDP\_20170215**  
**15 February 2017**

Sheet  
Reference  
Number  
6 of 97