



LWRP: 2.4  
Gage Reading: BR:25.8D:16.9 USED:24.3 NGVD  
Sea Conditions: SMOOTH  
Vessel Name: LAFOURCHE  
Survey Type: OT  
Sounding Frequency\*\*\*: HIGH

0' and above  
0' to -5'  
-5' to -10'  
-10' to -20'  
-20' to -30'  
-30' to -35'  
-35' to -40'  
-40' to -45'  
-45' and below

0 500 1,000 1,500 2,000 2,500

### MISSISSIPPI RIVER - B.R. TO GULF SARDINE POINT RECON MR\_06\_SDP\_20180606\_CS

06 June 2018

Sheet  
Reference  
Number  
6 of 97

Revision Number:  
3.12-20160811

DISTRIBUTION STATEMENT: The data represents the results of data collection/processing by a specific US Army Corps of Engineers activity and indicates the general existing conditions. Such data is not necessarily current or accurate. The user is responsible for the results of any application of the data for other than its intended purpose.

Data Constraints: Hydrographic survey data is subject to change due to several factors including but not limited to dredging activities and natural shoals and currents. The user is responsible for the hydrographic conditions when developing the data after publication. This data is intended for U.S. Army Corps of Engineers internal purposes. It is not to be distributed outside the U.S. Army Corps of Engineers without permission from the U.S. Army Corps of Engineers.

U.S. ARMY CORPS OF ENGINEERS NEW ORLEANS DISTRICT	
Surveyed By:	DSIPS/OSH
Submitted:	
Recommended:	One Survey Section
Approved:	One Waterways Maintenance Section
Checked By:	AO

NOTES:  
Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum: Soundings are shown in feet and indicate depths below Low Water Reference Plane 2007 (NGVD).

Distances on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE crew.

2010 Aerial Photography data source: NAIP, USDA-FSA-APFO Aerial Photography Field Office.

Reference is N.O.A.A. Navigation Chart No. 11370.

\*\* Shoal sounding per Quarter per Reach.

\*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.