

Distribution Liability: The data represents the results of data collection/processing by a specific US Army Corps of Engineers activity and indicates the general existing conditions. As such, the user accepts the data as is and releases the US Army Corps of Engineers from all claims or damages resulting from the use of the data. The user is responsible for the results of any application of the data for other than its intended purpose.

Data Constraints: Hydrographic survey data is subject to change rapidly due to several factors including but not limited to dredging activity and natural shoaling and scouring processes. The US Army Corps of Engineers does not guarantee the accuracy of the hydrographic conditions shown on this map. The data is intended for U.S. Army Corps of Engineers internal use only. The information depicted on this map represents the results of a survey conducted on this date indicated and can only be considered to represent the general condition existing at that time.

U.S. ARMY CORPS OF ENGINEERS	
NEW ORLEANS DISTRICT	
Surveyed By:	DSPE _____
Submitted:	_____
Recommended:	One I Survey Section
Approved:	One I Waterways Maintenance Section
Checked By:	AO _____

MISSISSIPPI RIVER - B.R. TO GULF
GRANADA RECON
MR_10_GRA_20161206
06 December 2016

NOTES:

Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.




Vertical Datum: Soundings are shown in feet and indicate depths below Low Water Reference Plane 2007 (NGVD). Distances on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE crew. 2010 Aerial Photography data source: NAIP, USDA-FSA-APFO Aerial Photography Field Office.

Reference is N.O.A.A. Navigation Chart No. 11370.

** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.



Sheet Reference Number
10 of 97