



LEG

- Federal Navigation Channel
 - Federal Navigation Center Line
 - As-built Pipeline/Cable
 - Unconfirmed Pipeline/Cable
 - Project Depth Contour
 - ○ Cable Area
 - Placement Area
 - [] Anchorage Area
 - ⊗ Obstruction Point
 - ↗ Wrecks-Submerged
 - Borrow Area
 - Shoalest Sounding**
 - ★ Beacon, General
 - ◆ Red Navigation Buoy
 - ◆ Green Navigation Buoy

 LWRP: 1.7
Gage Reading: BR:7.71 D:5.91 USED:6.4 NGVD
Sea Conditions: CALM
Vessel Name: OB-167
Survey Type: CONDITION
Sounding Frequency***: HIGH

Sounding Frequency : HIGH

Feet

500 1,000 1,500 2,000 2,500

ES:

Horizontal Coordinate System:
• American Datum of 1983 (NAD83), projected to the State Plane
Coordinate System (SPCS). Louisiana South Zone. Distance units in U.S. Survey Feet

Vertical Datum:
Elevations are shown in feet and indicate depths below Low Water Reference Plane 2007 (NGVD).
Distances on the Mississippi River, above and below Head of Passes are shown

Location of navigation aids are base on and provided by the U.S. Coast Guard and USACE crew.

Aerial Photography data source: NAIP, USDA-FSA-AP

oalest Sounding per Quarter per Reach.

High frequency (200 kHz) survey data represents the first signal return at a sounding son and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

Sheet Reference Number

16 of 97

Revision Number:
3.8.0-20150202