



LEG

- Federal Navigation Channel
 - Federal Navigation Center Line
 - As-built Pipeline/Cable
 - Unconfirmed Pipeline/Cable
 - Project Depth Contour
 - ○ Cable Area
 - Placement Area
 - Anchorage Area
 - ⊗ Obstruction Point
 - ↗ Wrecks-Submerged
 - Borrow Area
 - Shoalest Sounding**
 - ★ Beacon, General
 - ◆ Red Navigation Buoy
 - ◆ Green Navigation Buoy

Green	0' and above
Yellow	0' to -5'
Orange	-5' to -10'
Cyan	-10' to -20'
Light Blue	-20' to -30'
Medium Blue	-30' to -35'
Darker Blue	-35' to -40'
Magenta	-40' to 45'
Grey	-45' and below

 LWRP: 1.7
Gage Reading: BR27.7D:18.7 USED:21.3 NGVD
Sea Conditions: CALM
Vessel Name: LAFOURCHE
Survey Type: CONDITION
Sounding Frequency***: HIGH



0 500 1,000 1,500 2,000 2,500

NOTES:

Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane
Alaska FIPS 102-1 Conformal Transverse Mercator U.S. Survey Foot

Vertical Datum:
Elevations are shown in feet and indicate depths below Low Water Reference Plane 2007 (NGVD).
Distances on the Mississippi River, above and below Head of Passes are shown
in mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE crew.

0 Aerial Photography data source: NAIP, USDA-FSA-A

Shoalest Sounding per Quarter per Reach.

High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

**Sheet
Reference
Number**

Revision Number:
3.8.0-20150202