

**LEGEND**

- Federal Navigation Channel
- Federal Navigation Center Line
- As-built Pipeline/Cable
- Unconfirmed Pipeline/Cable
- Project Depth Contour

LEGEND

- Cable Area
- Placement Area
- Anchorage Area
- ★ Beacon, General
- ◆ Obstruction Point
- ✗ Wrecks-Submerged

LEGEND

- Borrow Area
- Shoalest Sounding**
- Anchorage Area
- ★ Beacon, General
- ◆ Obstruction Point
- ✗ Wrecks-Submerged

LWRP:

Gage Reading: 1.7
Sea Conditions: BR:20.2 D:12.8 USED:14.9 NGVD
Vessel Name: CALM
Survey Type: MV LAFOURCHE CONDITION
Sounding Frequency***: HIGH

Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.
Vertical Datum: Soundings are shown in feet and indicate depths below Low Water Reference Plane 2007 (NGVD).
Distances on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.
The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE crew.
2010 Aerial Photography data source: NAIP, USDA-FSA-APFO Aerial Photography Field Office.
Reference is N.O.A.A. Navigation Chart No. 11370.
** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.
Vertical Datum: Soundings are shown in feet and indicate depths below Low Water Reference Plane 2007 (NGVD).
Distances on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.
The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE crew.
2010 Aerial Photography data source: NAIP, USDA-FSA-APFO Aerial Photography Field Office.
Reference is N.O.A.A. Navigation Chart No. 11370.
** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

Sheet
Reference
Number
16 of 97

Revision Number:
312-20160811

MISSISSIPPI RIVER - B.R. TO GULF
ALHAMBRA RECON
MR_16_ALH_20170328_CS
28 March 2017

U.S. ARMY CORPS OF ENGINEERS
NEW ORLEANS DISTRICT
Surveyed By: DS95
Submitted: _____
Plotted By: BD
Recommended: One I Survey Section
Approved: One I Waterways Maintenance Section
Checked By: AC

DISCLAIMER
Distribution liability: The data represents the results of data collection/processing for a specific US Army Corps of Engineers activity and indicates the general existing conditions as such. It is not to be used for legal purposes. The user accepts full responsibility for the use of the data and agrees to indemnify and hold the US Army Corps of Engineers harmless for any damages resulting from its use. The user is responsible for the results of any application of the data for other than its intended purpose.
Data Constraints: Hydrographic survey data is subject to change due to several factors including but not limited to dredging activity and natural shoals and currents. The user is responsible for the hydrographic conditions when developing the data. The information depicted on this map represents the results of a survey conducted on this date and can only be considered to represent the general condition existing at that time.
The information depicted on this map represents the results of a survey conducted on this date and can only be considered to represent the general condition existing at that time.

US Army Corps of Engineers
District: CEMVN