U.S. ARMY CORPS OF ENGINEERS 299,000 3,919,000 305,000 308,000 US Army Corps of Engineers District: CEMVN MISS. RIVER OUTLETS A BAPTISTE COLLETTE, MI OV_02_BAP_20231220_0 3,925,000 299,000 302,000 296,000 3,928,000 NOTES: Horizontal Coordinate System: VICINITY MAP North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. **LEGEND** Gage Reading: DM 16 VRS: 0.7 MLLW AVG. Soundings are shown in feet and indicate depths below Mean Lower Low Water Datum (MLLW). Datum relationships as of April 2023: -7.5' and above Sea Conditions: CALM --- Federal Navigation Channel Cable Area Borrow Area 0.0' NAVD88 (2009.55) = -0.51' MLLW (2002-2006) = 2.99' MLG Vessel Name: OB-169 -7.5' to -11.5' Shoalest Sounding** — Federal Navigation Center Line Placement Area Distances on the Mississippi River, above and below Head of Passes are shown Survey Type: at 1 mile intervals. -11.5' to -13.5' Sounding Frequency***: 24 As-built Pipeline/Cable Anchorage Area Beacon, General The location of navigation aids are base on and provided by the U.S. Coast Guard. -13.5' to -15.5' ∅ Obstruction Point Unconfirmed Pipeline/Cable 2018 Aerial Photography data source: Precision Aerial Reconnaissaince LLC. Red Navigation Buoy -15.5' to -19.5' Sheet — Project Depth Contour Wrecks-Submerged Reference Reference is N.O.A.A. Navigation Chart No. 11353. -19.5' and below Green Navigation Buoy 1,000 1,500 2,000 Number ** Shoalest Sounding per Quarter per Reach. 2 **of** 6 *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom Revison Number: material. Low frequency accuracies may vary depending on channel conditions and fathometer ibutors, and the GIS use community 4.2-20200420