

**US Army Corps of Engineers District: CEMVN**

**Access Constraints:** The United States Government furnishes these data and the recipient accepts and uses them with the express understanding that the data are not to be used for any purpose other than that for which they were originally collected, and that the data are not to be used for any purpose other than that for which they were originally collected, and that the data are not to be used for any purpose other than that for which they were originally collected.

**Vertical Datum:** Soundings are shown in feet and indicate depths below Mean Lower Low Water (MLLW, 12-16). Datum Relationships for gage 01525 as of March 2020: 0.0' NAVD83, 2009.55 = -0.53' MLLW = 2.97' MLG

**Distances on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.**


**The location of navigation aids are based on and provided by the U.S. Coast Guard.**

**2022 Aerial Photography data source: Optimal GEO (1998 DOQQ in green)**

**Reference is N.O.A. Navigation Chart No. 11361.**

**\*\* Shoalest Sounding per Quarter per Reach.**

**\*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.**



**U.S. ARMY CORPS OF ENGINEERS NEW ORLEANS DISTRICT**

**Submitted:** \_\_\_\_\_


**Recommended:** \_\_\_\_\_

**Approved:** \_\_\_\_\_

**Surveyed By:** JH & RCC


**Plotted By:** LLB

**Checked By:** MSK



**LEGEND**

--- Federal Navigation Channel	● Cable Area	□ Borrow Area	■ -10' and above
— Federal Navigation Center Line	□ Placement Area	● Shoalest Sounding**	■ -10' to -20'
— As-built Pipeline/Cable	□ Anchorage Area	★ Beacon, General	■ -20' to -30'
..... Unconfirmed Pipeline/Cable	⊗ Obstruction Point	◆ Red Navigation Buoy	■ -30' to -40'
— Project Depth Contour	⚓ Wrecks-Submerged	◆ Green Navigation Buoy	■ -40' to -45'
			■ -45' to -50'
			■ -50' to -55'
			■ -55' and below




**Gage Reading:** -0.8 MLLW @ PILOT TOWN @ 1100

**Sea Conditions:** CALM

**Vessel Name:** TOBIN

**Survey Type:** CONDITION, SB

**Sounding Frequency\*\*\*:** LOW



**NOTES:**

**Horizontal Coordinate System:** North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

**Vertical Datum:** Soundings are shown in feet and indicate depths below Mean Lower Low Water (MLLW, 12-16). Datum Relationships for gage 01525 as of March 2020: 0.0' NAVD83, 2009.55 = -0.53' MLLW = 2.97' MLG

**Distances on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.**

**The location of navigation aids are based on and provided by the U.S. Coast Guard.**

**2022 Aerial Photography data source: Optimal GEO (1998 DOQQ in green)**

**Reference is N.O.A. Navigation Chart No. 11361.**

**\*\* Shoalest Sounding per Quarter per Reach.**

**\*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.**

**MISSISSIPPI RIVER - B.R. TO GULF PILOTTOWN ANCHORAGE SW\_00\_PTA\_20231213\_CS**

**13 December 2023**

**Sheet Reference Number**

**4 of 13**

**Revision Number:** 4.2-20230429