



LEGEND

Symbol	Description	Depth Range
—	Federal Navigation Channel	-10' and above
—	Federal Navigation Center Line	-10' to -20'
—	As-built Pipeline/Cable	-20' to -30'
.....	Unconfirmed Pipeline/Cable	-30' to -40'
—	Project Depth Contour	-40' to -45'
○ ○	Cable Area	-45' to -50'
□	Placement Area	-50' to -55'
□□	Anchorage Area	-55' and below
⊗	Obstruction Point	
↗	Wrecks-Submerged	
□	Borrow Area	
●	Shoalest Sounding**	
★	Beacon, General	
◆	Red Navigation Buoy	
◆	Green Navigation Buoy	

S:
ntal Coordinate System:
American Datum of 1983 (NAD83), projected to the State Plane
nate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

All Datum: feet
Measurements are shown in feet and indicate depths below Mean Lower Low Water (MLLW, 12-14)
Relationships for gage 01525 as of March 2020:
AVD88_2000.55 = -0.52' MLLW = -2.97' MLC

ences on the Mississippi River, above and below Head of Passes are shown
in intervals.

Location of navigation aids are base on and provided by the U.S. Coast Guard.

Aerial Photography data source: Optimal GEO (1998 DOQQ in green)

nce is N.O.A.A. Navigation Chart No. 11361.

high frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

S.

**Sheet
Reference
Number**

Revision Number:
4.2-20200420
