



**US Army Corps
of Engineers
District: CEMVN**

Distribution Liability: The data represents the results of data collection/processing for a specific US Army Corps of Engineers activity and should not be used for general water resource management or navigation purposes. The user is responsible for the results of any application of the data to other than its intended purpose.

Data Constraints: Hydrographic survey data is subject to change rapidly due to several factors including burial, erosion, dredging, Army Corps of Engineers actions, and changes in the hydrographic conditions which develop after the date of publication. The data is intended for U.S. Army Corps of Engineers internal use. Public release of the data is not intended at this time.

U.S. ARMY CORPS OF ENGINEERS	
Survived By:	JH & RCG
Protected By:	TS
Checked By:	MSK
Submitted:	One I Survey Section
Recommended:	One I Survey Section
Approved:	One I Waterways Maintenance Section

MISSISSIPPI RIVER - B.R. TO GULF
SOUTHWEST PASS - SHEET 2
SW_02_SWP_20230807_CS_B2B
07 August 2023

**Sheet
Reference
Number**
2 of 13

Revision Number:
42-200420

NOTES:

Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum: Soundings are shown in feet and indicate depths below Mean Lower Low Water (MLLW). 12'-16'.

Gage Reading: 0.2 MLLW @ VENICE @ 0755

Sea Conditions: CALM

Vessel Name: TOBIN

Survey Type: CONDITION, SB

Sounding Frequency***: LOW

Scale: 0 to 2,500 Feet

** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.