



**US Army Corps
of Engineers
District: CEMVN**

DISCLAIMER
The data represents the results of data collection/processing for a specific US Army Corps of Engineers activity and/or product. The general existing condition of such areas is not necessarily indicated by the data furnished. The user is responsible for any application of the data to other than its intended purpose.
Data Constraints: Hydrographic survey data is subject to change rapidly due to several factors including burial, erosion, dredging, or changes in the hydrographic conditions which develop after the date of publication. The data is intended for U.S. Army Corps of Engineers use. Other users are advised to consult their own sources for the latest information. The data is provided "as is" without warranty of any kind, either express or implied, including but not limited to the warranties of merchantability, fitness for a particular purpose and non-infringement. The user agrees not to represent that the data may not be other than Government provided data. The user may not transfer these data onto another medium without also transferring this Disclaimer.

U.S. ARMY CORPS OF ENGINEERS NEW ORLEANS DISTRICT	Survived By: JTB & DBD
Submitted:	Protected By: RSI
Recommended: One I Survey Section	Checked By: MSK
Approved: One I Waterways Maintenance Section	

**MISSISSIPPI RIVER - B.R. TO GULF
SOUTHWEST PASS - SHEET 2
SW_02_SWP_20240228_CS_B2B**
28 February 2024

**Sheet
Reference
Number**
2 of 13

Revision Number:
42-200420

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.