



<u>LEGEND</u>	
— Federal Navigation Channel	○ Cable Area
— Federal Navigation Center Line	■ Placement Area
— As-built Pipeline/Cable	● Shoalest Sounding**
..... Unconfirmed Pipeline/Cable	□ Anchorage Area
— Project Depth Contour	★ Beacon, General
	◆ Red Navigation Buoy
	◆ Green Navigation Buoy
	◆ Wrecks-Submerged
	3 Fluff Thickness (feet)*
	-10' and above
	-10' to -20'
	-20' to -30'
	-30' to -40'
	-40' to -45'
	-45' to -50'
	-50' to -55'
	-55' and below

Gage Reading: 2.1 MLLW @ VENICE (01480) @ 0720
 Vertical Datum: ROUGH
 Sea Conditions: TOBIN
 Vessel Name: CONDITION, SB
 Survey Type: Sounding Frequency***: LOW

 Feet
 0 500 1,000 1,500 2,000 2,500

NOTES:
 Horizontal Coordinate System:
 North American Datum of 1983 (NAD83), projected to the State Plane
 Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.
 Datum Relationships for gage 01480 as of March 2020:
 0.0' NAVD88, 2009.55 -0.53' MLLW = 2.97' MLG

Distances on the Mississippi River, above and below Head of Passes are shown
 at 1 mile intervals.
 The location of navigation aids are base on and provided by the U.S. Coast Guard.

2022 Aerial Photography data source: Optimal GEO (1998 DOQQ in green)
 Reference is N.O.A.A. Navigation Chart No. 11361.

** Shoalest Sounding per Quarter per Reach.
*** High frequency (200 kHz) survey data represents the first signal return at a sounding
 location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz)
 survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom
 material. Low frequency accuracies may vary depending on channel conditions and fathometer
 settings.



US Army Corps
of Engineers
District: CEMVN

Distribution liability: The data represents the results of data collection/processing for a specific US Army Corps of Engineers activity and includes the general existing condition. Such, specification, and accuracy are not guaranteed. The user is responsible for any application of the results of any use of any portion of any of the application of the data to other than its intended purpose.
 Data Constraints: Hydrographic survey data is subject to change rapidly due to several factors including burial rates to dredging Army Corps of Engineers activities as well as changes in the hydrographic conditions which develop after the date of publication. The data is intended for U.S. Army Corps of Engineers internal use. Public release should not be made until such time.

U.S. ARMY CORPS OF ENGINEERS	
NEW ORLEANS DISTRICT	
Surveyed By:	LBB & MGF
Submitted:	
Recommended:	One Survey Section
Approved:	One Waterways Maintenance Section

MISSISSIPPI RIVER - B.R. TO GULF
SOUTHWEST PASS - SHEET 3
SW_03_SWP_20240621_CS
 21 June 2024

Sheet Reference Number
 3 of 13

Revision Number:
 42-2000420