



LEGEND

— Federal Navigation Channel	○ ○ Cable Area	□ Borrow Area	-10' and above
— Federal Navigation Center Line	□ Placement Area	● Shoalest Sounding**	-10' to -20'
— As-built Pipeline/Cable	□ Anchorage Area	★ Beacon, General	-20' to -30'
..... Unconfirmed Pipeline/Cable	⊗ Obstruction Point	◆ Red Navigation Buoy	-30' to -40'
— Project Depth Contour	↗ Wrecks-Submerged	◆ Green Navigation Buoy	-40' to -45'
			-45' to -48.5'
			-48.5' to -55'
			-55' and below

,000

Coordinate System:
American Datum of 1983 (NAD83), projected to the State Plane
Coordinate System (SPCS). Louisiana South Zone. Distance units in U.S. Survey Feet.

Datum:
Gages are shown in feet and indicate depths below Mean Lower Low Water (MLLW, 07-11).
Relationships for gage 01525 as of July 2015:

Passes on the Mississippi River, above and below Head of Passes are shown at intervals.

tion of navigation aids are base on and provided by the U.S. Coast Guard

Aerial Photography data source: Precision Aerial Reconnaissance, LLC (1998 DOQQ) in grayscale

This is N O A A Navigation Chart No. 11361

frequency (200 kHz) survey data represents the first signal return at a sounding and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom. Low frequency accuracies may vary depending on channel conditions and fathometer

**Sheet
Reference
Number**

Revision Number:
3.12-20160811