



US Army Corps
of Engineers
District: CEMVN

Distribution Liability: The data represents the results of data collection/processing for a specific U.S. Army Corps of Engineers activity and/or product. The data is provided "as is" without warranty, expressed or implied, including the warranties of merchantability, fitness for a particular purpose, and non-infringement. The user is responsible for the results of any application of the data to other than its intended purpose.

Data Constraints: Hydrographic survey data is subject to change rapidly due to several factors including but not limited to dredging activities, changes in river bed material, and hydrographical conditions which develop after the date of publication. The data is intended for U.S. Army Corps of Engineers internal use. Public release of the data is not intended.

Data Disclaimer: The information depicted on this map represents the results of a survey conducted on the date indicated and can only be considered b reproducible in the general condition existing at the time.

| U.S. ARMY CORPS OF ENGINEERS | |
|------------------------------------|------------------------|
| Submitted: | Surveyed by: JTB & TDB |
| Recommended: | Protected by: RSL |
| Approved: | Checked by: NSK |
| One: Waterways Maintenance Section | One: Survey Section |

MISSISSIPPI RIVER - B.R. TO GULF
SOUTHWEST PASS - SHEET 4
SW_04_SWP_20180516_CS
16 May 2018

Sheet
Reference
Number
4 of 13

Revision Number:
312-20160811

Notes:

Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum: Soundings are shown in feet and indicate depths below Mean Lower Low Water (MLLW, 07-11). Datum Relationships for gage 01525 as of July 2015: 0.0' NAVD88 = -0.3' MLLW = 3.20' MLG

Distances on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard.

2016 Aerial Photography data source: Precision Aerial Reconnaissance, LLC (1998 DOQQ in green)

Reference is N.O.A.A. Navigation Chart No. 11361.

** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.