



Distribution Liability: The data represents the results of data collection/processing for a specific U.S. Army Corps of Engineers activity and should be used for that purpose only. Such use is subject to the terms and conditions of the data source. The user is responsible for the results of any application of the data to other than its intended purpose.

Data Constraints: Hydrographic survey data is subject to change rapidly due to several factors including burial, erosion or dredging. Army Corps of Engineers does not guarantee the accuracy of hydrographic conditions which develop after the date of publication. This data is intended for U.S. Army Corps of Engineers internal use. Public release of this data is not intended at this time.

| U.S. ARMY CORPS OF ENGINEERS<br>NEW ORLEANS DISTRICT |                       |
|--|-----------------------|
| Submitted:   | Surveyed By: HN & TDG |
| Recommended:   | Protected By: TS      |
| Approved:  | Checked By: NSK       |
| One: Waterways Maintenance Section                   | One: Survey Section   |

**MISSISSIPPI RIVER - B.R. TO GULF  
SOUTHWEST PASS - SHEET 4  
SW\_04\_SWP\_20180720\_CS**  
20 July 2018

Sheet  
Reference  
Number  
4 of 13

Revision Number:  
312-20160811

**NOTES:**  
Horizontal Coordinate System:  
North American Datum of 1983 (NAD83), projected to the State Plane  
Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:  
Soundings are shown in feet and indicate depths below Mean Lower Low Water (MLLW, 07-11).  
Datum Relationships for gage 01525 as of July 2015:  
0.0' NAVD88 = -0.3' MLLW = 3.20' MLG

Distances on the Mississippi River, above and below Head of Passes are shown  
at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard.

2016 Aerial Photography data source: Precision Aerial Reconnaissance, LLC (1998 DOQQ in green)

Reference is N.O.A.A. Navigation Chart No. 11361.

\*\* Shoalest Sounding per Quarter per Reach.

\*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.