



US Army Corps
of Engineers
District: CEMVN

Distribution Liability: The data represents the results of data collection/processing for a specific U.S. Army Corps of Engineers activity and should not be used for general engineering or surveying purposes. The user is responsible for the results of any application of the data to other than its intended purpose. Data Constraints: Hydrographic survey data is subject to change resulting in several areas including buried material to dredge. Army Corps of Engineers does not guarantee the accuracy of the hydrographic conditions which develop after the date of publication. This data is intended for use by the Army Corps of Engineers and its contractors and is not available to the public. The information depicted on this map represents the results of a survey conducted on the date indicated and can only be considered reliable for the general condition existing at that time.

U.S. ARMY CORPS OF ENGINEERS	
Submitted:	Surveyed By: JTB & MGF
Recommended:	Protected By: 1S
Approved:	Checked By: NSK

MISSISSIPPI RIVER - B.R. TO GULF
SOUTHWEST PASS - SHEET 4
SW_04_SWP_20180815_CS
15 August 2018

Sheet
Reference
Number
4 of 13

Revision Number:
312-20160811

Notes:

Horizontal Coordinate System: NAD83 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum: Soundings are shown in feet and indicate depths below Mean Lower Low Water (MLLW, 07-11). Datum Relationships for gage 01525 as of July 2015: 0.0' NAVD88 = -0.3' MLLW = 3.20' MLG

Distances on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard.

2016 Aerial Photography data source: Precision Aerial Reconnaissance, LLC (1998 DOQQ in green)

Reference is N.O.A.A. Navigation Chart No. 11361.

** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.