



LEGEND

— Federal Navigation Channel	○ ○ Cable Area	□ Borrow Area	-10' and above
— Federal Navigation Center Line	□ Placement Area	● Shoalest Sounding**	-10' to -20'
— As-built Pipeline/Cable	[] Anchorage Area	★ Beacon, General	-20' to -30'
..... Unconfirmed Pipeline/Cable	⊗ Obstruction Point	◆ Red Navigation Buoy	-30' to -40'
— Project Depth Contour	➤ Wrecks-Submerged	◆ Green Navigation Buoy	-40' to -45'
			-45' to -48.5'
			-48.5' to -55'
			-55' and below

 Gage Reading: 2.0 MLLW @ PILOT TOWN @ 1015
Sea Conditions: CALM, SAND WAVES
Vessel Name: TECHE
Survey Type: CONDITION, SB
Sounding Frequency***: LOW

NOTES:
Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane
Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Lower Low Water (MLLW, 07-11).
Datum Relationships for gage 01525 as of July 2015:
0.0' NAVD88 = -0.3' MLLW = 3.20' MLG

Distances on the Mississippi River, above and below Head of Passes are shown
(Head of Passes is at mile 0)

The location of navigation aids are base on and provided by the U.S. Coast Guard.

2016 Aerial Photography data source: Precision Aerial Reconnaissance LLC (1998 DOQQ in grey).

© 2016 Pearson Education, Inc. All Rights Reserved. May not be copied, scanned, or duplicated, in whole or in part. Due to electronic rights, some third party content may be suppressed from the eBook and/or eChapter(s). Editorial review has determined that any suppressed content does not materially affect the overall learning experience. Pearson is not affiliated with the content provider.

Reference is N.O.A.A. Navigation Chart No. 11361.

**** Shoalest Sounding per Quarter per Reach.**

*** High frequency (200 kHz) survey data represents the first signal return at a sounding

location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz)

survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer

settings.

Digitized by srujanika@gmail.com

(n)

**Sheet
Reference
Number**

4 of 13

—

Revision Number:

4.0-201907022
