



LEGEND

Symbol	Description	Depth Range
—	Federal Navigation Channel	
—	Federal Navigation Center Line	
—	As-built Pipeline/Cable	
.....	Unconfirmed Pipeline/Cable	
—	Project Depth Contour	
○ ○	Cable Area	
□	Placement Area	
[]	Anchorage Area	
⊗	Obstruction Point	
↗	Wrecks-Submerged	
□	Borrow Area	
●	Shoalest Sounding**	
★	Beacon, General	
◆	Red Navigation Buoy	
◆	Green Navigation Buoy	
-10' and above		
-10' to -20'		
-20' to -30'		
-30' to -40'		
-40' to -45'		
-45' to -48.5'		
-48.5' to -55'		
-55' and below		

Gage Reading: 1.9 MLLW @ PILOT TOWN @ 1230
Sea Conditions: CALM
Vessel Name: TECHE
Survey Type: CONDITION, SB
Sounding Frequency***: LOW

Feet

0 500 1,000 1,500 2,000 2,500

S:
ntal Coordinate System:
American Datum of 1983 (NAD83), projected to the State Plane
nate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

All Datum:
Readings are shown in feet and indicate depths below Mean Lower Low Water (MLLW, 07-11).
Relationships for gage 01525 as of July 2015:
AVD88 = -0.3' MLLW = 3.20' MLG

ences on the Mississippi River, above and below Head of Passes are shown at 1-mile intervals.

Location of navigation aids are base on and provided by the U.S. Coast Guard.

Aerial Photography data source: Precision Aerial Reconnaissance, LLC (1998 DOQ)

Aerial Photography data source: Precision Aerial Reconnaissance, LLC (1998) DC

nce is N.O.A.A. Navigation Chart No. 11361.

allest Sounding per Quarter per Reach.

High frequency (200 kHz) survey data represents the first signal return at a sounding and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

Sheet
Reference
Number

Revision Number:
4.0-201907022