



Gage Reading: 1.0 MLLW @ PILOT TOWN @ 1225
Sea Conditions: CALM
Vessel Name: BLANCHARD
Survey Type: CONDITION, SB
Sounding Frequency***: LOW

Feet

US Army Corps of Engineers
District: CEMVN

Distribution liability: The data represents the results of data collection processing by a specific US Army Corps of Engineers activity and includes the general existing conditions. Such data is not necessarily suitable for any particular purpose. The user is responsible for the results of any application of the data for other than its intended purpose.

Data Constraints: Hydrographic survey data is subject to change rapidly due to several factors including, but not limited to dredging operations, subsidence, or changes in the river channel. The data is intended for use in engineering studies and does not represent the results of a survey conducted on the date indicated and can only be considered reliable when used in conjunction with the latest available survey data.

U.S. ARMY CORPS OF ENGINEERS
NEW ORLEANS DISTRICT

Submitted By: JH & BBD	Surveyed By: JH & BBD
Recommended By: TS	Plotted By: TS
Chief Survey Section: Office of Waterways Maintenance Section	Checked By: MSK
Approved: Chief, Waterways Maintenance Section	Approved: Chief, Waterways Maintenance Section

MISSISSIPPI RIVER - B.R. TO GULF
SOUTHWEST PASS - SHEET 4
SW_04_SWP_20210512_CS_PRO

12 May 2021

Sheet Reference Number
4 of 13

Revision Number: 4-1-20191105

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.