





LEGEND				3 Fluff Thickness (feet)*	-10' and above
Federal Navigation Channel	Cable Area	Borrow Area	Shoalest Sounding**	-10' to -20'	-20' to -30'
Federal Navigation Center Line	Placement Area	Beacon, General	Red Navigation Buoy	-30' to -40'	-40' to -45'
As-built Pipeline/Cable	Anchorage Area	Green Navigation Buoy	Wrecks-Submerged	-45' to -50'	-50' to -55'
Unconfirmed Pipeline/Cable	Obstruction Point			-55' and below	
Project Depth Contour					



NOTES:

Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane
Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Lower Low Water (MLLW, 12-16).
Datum Relationships for gage 01525 as of March 2020:
0.0' NAVD88, 2009.55 = -0.53' MLLW = 2.97' MLG

Distances on the Mississippi River, above and below Head of Passes are shown
at 1 mile intervals.

The location of navigation aids are based on and provided by the U.S. Coast Guard.

2024 Aerial Photography data source: Optimal GEO (1998 DOQQ in green)

Reference is N.O.A.A. Navigation Chart No. 11361.

**** Shoalest Sounding per Quarter per Reach.**

***** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and bathymetry setting.**

**Sheet
Reference
Number**
5 of 13