



#### **OTES:**

Horizontal Coordinate System:  
North American Datum of 1983 (NAD83), projected to the State Plane  
Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

**Critical Datum:**  
Readings are shown in feet and indicate depths below Mean Lower Low Water (MLLW, 07-1999). Relationship for page 01525 as of July 2015.

um Relationships for gage 01525 as of July 2015:  
NAVD88 = -0.3' MLLW = 3.20' MLG

stances on the Mississippi River, above and below Head of Passes are shown

mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard.

6 Aerial Photography data source: Precision Aerial Reconnaissance, LLC (1998 DOQQ in

erence is N.O.A.A. Navigation Chart No. 11361.

choalest Sounding per Quarter per Reach.

High frequency (200 kHz) survey data represents the first signal return at a sounding

ation and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) key data normally penetrates through this "fluff" layer to depict elevations of concealed layers.

Survey data normally penetrates through this null layer to depict elevations of consolidated material. Low frequency accuracies may vary depending on channel conditions and fathometer

ings.

[View Details](#) | [Edit](#) | [Delete](#)

She  
Refer  
Num

5 of

1

Revision N

3.12-201608

Page 1