



LEGEND

— Federal Navigation Channel	○ ○ Cable Area	□ Borrow Area	-10' and above
— Federal Navigation Center Line	□ Placement Area	● Shoalest Sounding**	-10' to -20'
— As-built Pipeline/Cable	□ Anchorage Area	★ Beacon, General	-20' to -30'
..... Unconfirmed Pipeline/Cable	⊗ Obstruction Point	◆ Red Navigation Buoy	-30' to -40'
— Project Depth Contour	→ Wrecks-Submerged	◆ Green Navigation Buoy	-40' to -45'
			-45' to -48.5'
			-48.5' to -55'
			-55' and below

• TES:

Coordinate System:
Datum of 1983 (NAD83), projected to the State Plane
System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

shown in feet and indicate depths below Mean Lower Low Water (MLLW, 07-1962).
Shipments for gage 01525 as of July 2015:

Mississippi River, above and below Head of Passes are shown

Navigation aids are base on and provided by the U.S. Coast Guard.

Photography data source: Precision Aerial Reconnaissance, LLC (1998 DOQQ imagery).

© A.A. Navigation Chart No. 11361

Spending per Quarter per Reach

cy (200 kHz) survey data represents the first signal return at a sounding

include suspended solids, known as "fluff", if present. Low frequency (24 kHz) usually penetrates through this "fluff" layer to depict elevations of consolidated bottom. Frequency accuracies may vary depending on channel conditions and fathometer settings.

For more information about the study, please contact Dr. John Smith at (555) 123-4567 or via email at john.smith@researchinstitute.org.

**Shee
Referer
Numb**

Revison Num