



LEGEND

| | | | |
|----------------------------------|---------------------|-------------------------|------------------|
| — Federal Navigation Channel | ● Cable Area | □ Borrow Area | ■ -10' and above |
| — Federal Navigation Center Line | ■ Placement Area | ● Shoalest Sounding** | ■ -10' to -20' |
| — As-built Pipeline/Cable | ⊗ Anchorage Area | ★ Beacon, General | ■ -20' to -30' |
| Unconfirmed Pipeline/Cable | ⊗ Obstruction Point | ◆ Red Navigation Buoy | ■ -30' to -40' |
| — Project Depth Contour | ⚓ Wrecks-Submerged | ◆ Green Navigation Buoy | ■ -40' to -45' |
| | | | ■ -45' to -48.5' |
| | | | ■ -48.5' to -55' |
| | | | ■ -55' and below |

Gage Reading: 1.1 MLLW @ HEAD OF PASSES @ 0840

Sea Conditions: CALM, FLUFF

Vessel Name: BLANCHARD

Survey Type: CONDITION, SB

Sounding Frequency***: LOW

NOTES:
 Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.
 Vertical Datum: Soundings are shown in feet and indicate depths below Mean Lower Low Water (MLLW, 07-11). Datum Relationships for gage 01545 as of July 2015: 0.0' NAVD83 = -0.18' MLLW = 3.32' MLG
 Distances on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.
 The location of navigation aids are base on and provided by the U.S. Coast Guard.
 2016 Aerial Photography data source: Precision Aerial Reconnaissance, LLC (1998 DOQQ in green)
 Reference is N.O.A. Navigation Chart No. 11361.
 ** Shoalest Sounding per Quarter per Reach.
 *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.



DISTRIBUTION
 The data represented on this map is the result of a specific US Army Corps of Engineers collection/processing for a specific purpose and is only valid for its intended use. Content, time and accuracy specifications. The user is responsible for the results of any application of the data for other than its intended purpose.
 Data Constants: Hydrographic survey data is subject to change rapidly due to several factors including but not limited to dredging activities, channel migration, and erosion. The US Army Corps of Engineers accepts no responsibility for changes in the hydrographical conditions which develop after the date of the collection/processing of the data. Prudent mariners should not rely solely upon it.

ACCESS
 The United States Government furnishes these data and the recipient accepts and uses them with the express understanding that no warranty, expressed or implied, concerning the accuracy, completeness, reliability, usability or suitability for any particular purpose of the data is made. The recipient is liable for any use of the data under no liability whatsoever to any person by reason of any use of the data. These data are being released to the public under the provisions of the Government Information Policy. The recipient may not transfer these data to others without also transferring this disclaimer.
 The information depicted on this map represents the results of a collection/processing of data which has been considered and found to be reliable for the purposes intended.

U.S. ARMY CORPS OF ENGINEERS
NEW ORLEANS DISTRICT

| | |
|---|-----------------------|
| Submitted: | Surveyed By: JH & DBD |
| Recommended: Chief Survey Section | Plotted By: TSS |
| Approved: Chief Waterways Maintenance Section | Checked By: MSK |

MISSISSIPPI RIVER - B.R. TO GULF
SOUTHWEST PASS - SHEET 6
 SW_06_SWP_20180607_CS
 07 June 2018

Sheet Reference Number
 6 of 13