


| LEGEND                           |                     |                         |                  |
|----------------------------------|---------------------|-------------------------|------------------|
| --- Federal Navigation Channel   | ○ Cable Area        | □ Borrow Area           | ■ -10' and above |
| — Federal Navigation Center Line | □ Placement Area    | ● Shoalest Sounding**   | ■ -10' to -20'   |
| — As-built Pipeline/Cable        | □ Anchorage Area    | ★ Beacon, General       | ■ -20' to -30'   |
| ..... Unconfirmed Pipeline/Cable | ⊗ Obstruction Point | ◆ Red Navigation Buoy   | ■ -30' to -40'   |
| — Project Depth Contour          | ★ Wrecks-Submerged  | ◆ Green Navigation Buoy | ■ -40' to -45'   |
|                                  |                     |                         | ■ -45' to -50'   |
|                                  |                     |                         | ■ -50' to -55'   |
|                                  |                     |                         | ■ -55' and below |



**NOTES:**  
 Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.  
 Vertical Datum: 0.0' NAVD83, 2009.55 = -0.32' MLLW = 3.18' MGLG  
 Soundings are shown in feet and indicate depths below Mean Lower Low Water (MLLW, 12-16). Datum Relationships for gage 01545 as of March 2020: 0.0' NAVD83, 2009.55 = -0.32' MLLW = 3.18' MGLG  
 Distances on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.  
 The location of navigation aids are base on and provided by the U.S. Coast Guard.  
 2022 Aerial Photography data source: Optimal GEO (1998 DOQQ in green)  
 Reference is N.O.A. Navigation Chart No. 11361.  
 \*\* Shoalest Sounding per Quarter per Reach.  
 \*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.



**DISTRIBUTION LIABILITY:** The data represents the results of data collection/processing for a specific US Army Corps of Engineers project. It is only valid for its intended use, content, time and accuracy specifications. The user is responsible for the results and accuracy of the data. Application of the data for other than its intended purpose is not warranted. Data Constants: Hydrographic survey data is subject to change rapidly due to several factors including but not limited to dredging, spoil, and channel shifts. The user is responsible for the accuracy of the data. The information depicted on the map represents the results of a survey conducted on the date shown. It is not intended to represent the general condition existing at that time.

| U.S. ARMY CORPS OF ENGINEERS<br>NEW ORLEANS DISTRICT |                           |                                     |
|--|---------------------------|-------------------------------------|
| Submitted:   | Surveyed By:<br>JTB & DBD | Checked By:<br>MSK                  |
| Recommended:   | Plotted By:<br>RSL        |                                     |
| Approved:  | Chart Survey Section      | Chart Waterways Maintenance Section |

**MISSISSIPPI RIVER - B.R. TO GULF  
 SOUTHWEST PASS - SHEET 6  
 SW\_06\_SWP\_20230808\_CS  
 08 August 2023**

**Sheet Reference Number  
 6 of 13**

Revision Number:  
 4.2-20230820