



LEGEND

Symbol	Description	Depth Range
—	Federal Navigation Channel	
—	Federal Navigation Center Line	
—	As-built Pipeline/Cable	
.....	Unconfirmed Pipeline/Cable	
—	Project Depth Contour	
○ ○	Cable Area	
□	Placement Area	
[]	Anchorage Area	
⊗	Obstruction Point	
↗	Wrecks-Submerged	
□	Borrow Area	
●	Shoalest Sounding**	
★	Beacon, General	
◆	Red Navigation Buoy	
◆	Green Navigation Buoy	
-10' and above		
-10' to -20'		
-20' to -30'		
-30' to -40'		
-40' to -45'		
-45' to -48.5'		
-48.5' to -55'		
-55' and below		

Gage Reading: 2.6 MLLW @ LIGHT-21 @ 1310
 Sea Conditions: CALM
 Vessel Name: BLANCHARD
 Survey Type: CONDITION, SB
 Sounding Frequency***: LOW

Feet

0	500	1,000	1,500	2,000	2,500
---	-----	-------	-------	-------	-------

NOTES:
Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane
Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Lower Low Water (MLLW, 07-11).
Datum Relationships for gage 01575 as of July 2015:
0.0' NAVD88 = 0.17' MLLW = 3.67' MLG

Distances on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard.

2016 Aerial Photography data source: Precision Aerial Reconnaissance, LLC (1998 DOQQ in green)

Reference is N.O.A.A. Navigation Chart No. 11361.

** Shoalest Sounding per Quarter per Reach.
*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

Sheet Reference Number

Revision Number:
4.0-201907022