


LEGEND

Symbol	Description	Depth Range
—	Federal Navigation Channel	
—	Federal Navigation Center Line	
—	As-built Pipeline/Cable	
.....	Unconfirmed Pipeline/Cable	
—	Project Depth Contour	
○ ○	Cable Area	
□	Placement Area	
[]	Anchorage Area	
⊗	Obstruction Point	
↗	Wrecks-Submerged	
■	Borrow Area	-10' and above
●	Shoalest Sounding**	-10' to -20'
★	Beacon, General	-20' to -30'
◆	Red Navigation Buoy	-30' to -40'
◆	Green Navigation Buoy	-40' to -45'
◆	Red Navigation Buoy	-45' to -48.5'
◆	Green Navigation Buoy	-48.5' to -55'
■	Borrow Area	-55' and below

 Gage Reading: 2.2 MLLW @ LIGHT 21 @ 0925
Sea Conditions: CALM
Vessel Name: OB-173
Survey Type: CONDITION, SB
Sounding Frequency***: LOW



A horizontal scale bar representing distance in feet. The bar is divided into segments by vertical tick marks. The labels indicate distances of 0, 500, 1,000, 1,500, 2,000, and 2,500 feet. The first segment from 0 to 500 is black with a white center. Subsequent segments are white with black outlines.

NOTES:
Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane
Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Lower Low Water (MLLW, 07-11).
Datum Relationships for gage 01575 as of July 2015:
0.0' NAVD88 = 0.17' MLLW = 3.67' MLG

Distances on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard.

2016 Aerial Photography data source: Precision Aerial Reconnaissance, LLC (1998 DOQ)

Reference is N.O.A.A. Navigation Chart No. 11361

** Check out Scoutingunner Quarter on Beach

*** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

Sheet Reference Number

Revision Number:
4.0-201907022