


<b>LEGEND</b>	
— Federal Navigation Channel	○ Cable Area
— Federal Navigation Center Line	■ Placement Area
— As-built Pipeline/Cable	□ Anchorage Area
..... Unconfirmed Pipeline/Cable	⊗ Obstruction Point
— Project Depth Contour	★ Beacon, General
	◆ Red Navigation Buoy
	◆ Green Navigation Buoy
	■ Borrow Area
	● Shoalest Sounding**
	■ Anchorage Area
	⊗ Obstruction Point
	★ Beacon, General
	◆ Red Navigation Buoy
	◆ Green Navigation Buoy
	-10' and above
	-10' to -20'
	-20' to -30'
	-30' to -40'
	-40' to -45'
	-45' to -50'
	-50' to -55'
	-55' and below

Gage Reading: 1.6 MLLW @ LIGHT 21 @ 1115  
 Sea Conditions: CHOPPY, FLUFF  
 Vessel Name: BLANCHARD  
 Survey Type: CONDITION, SB  
 Sounding Frequency\*\*\*: LOW

0 500 1,000 1,500 2,000 2,500



Feet

**NOTES:**  
 Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum: Soundings are shown in feet and indicate depths below Mean Lower Low Water (MLLW-12-15). Datum Relationships for gage 01575 as of March 2020: 0.0' NAVD88, 2009.55 ± 0.1' MLLW = 3.60' MLG

Distances on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard.

2016 Aerial Photography data source: Precision Aerial Reconnaissance, LLC (1998 DOQQ in green)

Reference is N.O.A.A. Navigation Chart No. 11361.

\*\* Shoalest Sounding per Quarter per Reach.

\*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

**Sheet Reference Number**  
8 of 13

Revision Number:  
4-1-20191105

**US Army Corps of Engineers District: CEMVN**

**DISCLAIMER**  
 The data represents the results of data collection processing by a specific US Army Corps of Engineers activity and includes the general existing conditions as such. The user is responsible for the results of any application of the data for other than its intended purpose.  
**Data Constraints:** Hydrographic survey data is subject to change rapidly due to several factors including but not limited to dredging operations, changes in river flows, and changes in the hydrographical conditions which develop after the date of publication. This data is intended for U.S. Army Corps of Engineers use only and shall not be used open to the public.

**U.S. ARMY CORPS OF ENGINEERS NEW ORLEANS DISTRICT**  
 Surveyed By: JTB & DBD  
 Printed By: TS  
 Checked By: MSK  
 Submitted: \_\_\_\_\_  
 Recommended: \_\_\_\_\_  
 Chief Survey Section: \_\_\_\_\_  
 Approved: \_\_\_\_\_  
 Chief Waterways Maintenance Section: \_\_\_\_\_

**MISSISSIPPI RIVER - BR. TO GULF SOUTHWEST PASS - SHEET 8 SW\_08\_SWP\_20210722\_CS\_PRO**  
 22 July 2021