


<u>LEGEND</u>	
— Federal Navigation Channel	○ Cable Area
— Federal Navigation Center Line	■ Placement Area
— As-built Pipeline/Cable	□ Anchorage Area
..... Unconfirmed Pipeline/Cable	★ Beacon, General
— Project Depth Contour	⊗ Obstruction Point
	◆ Red Navigation Buoy
	◆ Green Navigation Buoy
	♂ Wrecks-Submerged
	-10' and above
	-10' to -20'
	-20' to -30'
	-30' to -40'
	-40' to -45'
	-45' to -50'
	-50' to -55'
	-55' and below

Gage Reading: 0.8 MLLW @ LIGHT 21 @ 1120  
Sea Conditions: CALM  
Vessel Name: BLANCHARD & BEAUVAIS  
Survey Type: CONDITION, SB  
Sounding Frequency\*\*\*: LOW

0 500 1,000 1,500 2,000 2,500 Feet



**NOTES:**  
Horizontal Coordinate System:  
North American Datum of 1983 (NAD83), projected to the State Plane  
Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:  
Soundings are shown in feet and indicate depths below Mean Lower Low Water (MLLW-12-15).  
Datum Relationships for gage 01575 as of March 2020:  
0.0' NAVD88, 2009.55 ± 0.1' MLLW = 3.60' MLG

Distances on the Mississippi River, above and below Head of Passes are shown  
at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard.  
2016 Aerial Photography data source: Precision Aerial Reconnaissance, LLC (1998 DOQQ in green)  
Reference is N.O.A.A. Navigation Chart No. 11361.

\*\* Shoal sounding per quarter per reach.

\*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding  
location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz)  
survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom  
material. Low frequency accuracies may vary depending on channel conditions and fathometer  
settings.



Distribution liability: The data represents the results of data collection processing by a specific US Army Corps of Engineers activity and includes the general existing conditions. Such results are not necessarily survey grade or suitable for engineering specifications. The user is responsible for the results of any application of the data for other than its intended purpose.

Data Constraints: Hydrographic survey data is subject to change rapidly due to several factors including but not limited to dredging, navigation, and changes in the river bed. The user is responsible for keeping the data current and for determining whether the data is suitable for the intended use.

The information depicted on this map represents the results of a survey conducted on the date indicated and can only be considered to be current in the general condition existing at that time.

U.S. ARMY CORPS OF ENGINEERS NEW ORLEANS DISTRICT	
Surveyed By:	JTB & JJC
Plotted By:	TS
Checked By:	MSK
Submitted:	
Recommended:	
Chief, Survey Section:	
Approved:	
Chief, Waterways Maintenance Section	

**MISSISSIPPI RIVER - B.R. TO GULF  
SOUTHWEST PASS - SHEET 8  
SW\_08\_SWP\_20220125\_CS\_PRO**  
25 January 2022

Sheet  
Reference  
Number  
**8 of 13**

Revision Number:  
42-2004020