



LEGEND

- - - Federal Navigation Channel	● Cable Area	□ Borrow Area	■ -10' and above
— Federal Navigation Center Line	▭ Placement Area	● Shoalest Sounding**	■ -10' to -20'
— As-built Pipeline/Cable	⊠ Anchorage Area	☆ Beacon, General	■ -20' to -30'
····· Unconfirmed Pipeline/Cable	⊗ Obstruction Point	◇ Red Navigation Buoy	■ -30' to -40'
— Project Depth Contour	⚓ Wrecks-Submerged	◇ Green Navigation Buoy	■ -40' to -45'
			■ -45' to -50'
			■ -50' to -55'
			■ -55' and below

NOTES:

Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum: Soundings are shown in feet and indicate depths below Mean Lower Low Water (MLLW, 12-15). Datum Relationships for gage 01575 as of March 2020: 0.0' NAVD88, 2009.55 = 0.10' MLLW = 3.60' MLG

Distances on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard.

2022 Aerial Photography data source: Optimal GEO (1998 DOQQ in green)

Reference is N.O.A. Navigation Chart No. 11361.

** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

Gage Reading: 1.4 MLLW @ LIGHT 21 @ 1140

Sea Conditions: CALM, FLUFF

Vessel Name: BLANCHARD

Survey Type: CONDITION, SB

Sounding Frequency***: LOW



DISTRIBUTION STATEMENT: This data represents the results of data collection/processing for a specific US Army Corps of Engineers project and is only valid for its intended use, content, time and accuracy specifications. The user is responsible for the results obtained from this data. Approximation of the data for other than its intended purpose.

DATA CONSTRAINTS: Hydrographic survey data is subject to change rapidly due to several factors including but not limited to dredging activities, sedimentation, and channel shifts. The US Army Corps of Engineers accepts no responsibility for changes in the hydrographic conditions which develop after the date of the original survey. Product remains should not be used to support any internal use. Product remains should not be used to support any internal use.

U.S. ARMY CORPS OF ENGINEERS
NEW ORLEANS DISTRICT

Submitted:	Surveyed By: JTB & DEB	Checked By: MSK
Recommended: Chet, Survey Section	Plotted By: TSS	
Approved: Chet, Waterways Maintenance Section		

**MISSISSIPPI RIVER - B.R. TO GULF
SOUTHWEST PASS - SHEET 8
SW_08_SWP_20230405_CS**

05 April 2023