



<u>LEGEND</u>	
— Federal Navigation Channel	○ Cable Area
— Federal Navigation Center Line	■ Placement Area
— As-built Pipeline/Cable	□ Anchorage Area
..... Unconfirmed Pipeline/Cable	★ Beacon, General
— Project Depth Contour	◆ Red Navigation Buoy
	◆ Green Navigation Buoy
	◆ Wrecks-Submerged
	-10' and above
	-10' to -20'
	-20' to -30'
	-30' to -40'
	-40' to -45'
	-45' to -50'
	-50' to -55'
	-55' and below

Gage Reading: 1.2 MLLW @ MM 7.5 LT-21 (01575) @ 0115
 Sea Conditions: CALM
 Vessel Name: TOBIN
 Survey Type: CONDITION, SB
 Sounding Frequency***: LOW

0 500 1,000 1,500 2,000 2,500
 Feet



NOTES:
 Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum: 0.0' NAVD88, 2009.55 ± 0.1' MLLW = 3.60' MLG

Datum Relationships for gage 01575 as of March 2020:
 Distances on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard.
 2022 Aerial Photography data source: Optimal GEO (1998 DOQQ in green)
 Reference is N.O.A.A. Navigation Chart No. 11361.

** Shoal sounding per quarter per reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.



Distribution liability: The data represents the results of data collection processing by a specific US Army Corps of Engineers activity and includes the general existing conditions as such. The user is responsible for the results of any application of any of the data for other than its intended purpose.

Data Constraints: Hydrographic survey data is subject to change rapidly due to several factors including, but not limited to dredging, Army Corps of Engineers actions which develop after the date of publication, and changes in the hydrographical conditions which develop after the date of publication. The user is advised to refer to the latest version of the hydrographical conditions which develop after the date of publication. The information provided on this map represents the results of a survey conducted on the date indicated and can only be considered to be valid for the period of time indicated.

U.S. ARMY CORPS OF ENGINEERS NEW ORLEANS DISTRICT	Surveyed By: JH & ROC
Submitted:	Plotted By: TS
Recommended:	Checked By: MSK
Chief, Waterways Maintenance Section	Approved: Chief, Waterways Maintenance Section

**MISSISSIPPI RIVER - BR. TO GULF
SOUTHWEST PASS - SHEET 8
SW_08_SWP_20240423_CS_PRO**
 23 April 2024

Sheet
Reference
Number
8 of 13

Revision Number:
42-2000420