


LEGEND

Symbol	Description	Depth Range
—	Federal Navigation Channel	-10' and above
—	Federal Navigation Center Line	-10' to -20'
—	As-built Pipeline/Cable	-20' to -30'
.....	Unconfirmed Pipeline/Cable	-30' to -40'
—	Project Depth Contour	-40' to -45'
○ ○	Cable Area	-45' to -50'
□	Placement Area	-50' to -55'
[]	Anchorage Area	-55' and below
⊗	Obstruction Point	
↗	Wrecks-Submerged	
□	Borrow Area	
●	Shoalest Sounding**	
★	Beacon, General	
◆	Red Navigation Buoy	
◆	Green Navigation Buoy	



Gage Reading: 2.2 MLLW @ MM 7.5 LT-21 (01575)
 Sea Conditions: CALM, FLUFF
 Vessel Name: BLANCHARD
 Survey Type: CONDITION, SB
 Sounding Frequency***: LOW

Feet

0 500 1,000 1,500 2,000 2,500

NOTES:
Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane
Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Lower Low Water (MLLW, 12-15).
Datum Relationships for gage 01575 as of March 2020:
0.0' NAVD88, 2009.55 = 0.10' MLLW = 3.60' MLG

Distances on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard.

2022 Aerial Photography data source: Optimal GEO (1998 DOQQ in green)

Reference is N.O.A.A. Navigation Chart No. 11361

Chart Sheet Soundings over Quarter mile Beach

" Shoalest Sounding per Quarter per Reach.

** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (

survey data normally penetrates through this "fluff" layer to depict elevations of consolidated material. Low frequency accuracies may vary depending on channel conditions and fatigued

settings.

**Sheet
Reference
Number**

Revision Number:
4.2-20200420