


| <b>LEGEND</b>                    |                         |
|----------------------------------|-------------------------|
| — Federal Navigation Channel     | ○ Cable Area            |
| — Federal Navigation Center Line | ■ Placement Area        |
| — As-built Pipeline/Cable        | □ Anchorage Area        |
| ..... Unconfirmed Pipeline/Cable | ★ Beacon, General       |
| — Project Depth Contour          | ⊗ Obstruction Point     |
|                                  | ◆ Red Navigation Buoy   |
|                                  | ◆ Green Navigation Buoy |
|                                  | ■ Shoal sounding**      |
|                                  | ● Wrecks-Submerged      |
|                                  | -10' and above          |
|                                  | -10' to -20'            |
|                                  | -20' to -30'            |
|                                  | -30' to -40'            |
|                                  | -40' to -45'            |
|                                  | -45' to -48.5'          |
|                                  | -48.5' to -55'          |
|                                  | -55' and below          |

Gage Reading: 2.6 MLLW @ LIGHT-14 @ 0945  
 Sea Conditions: CHOPPY  
 Vessel Name: BEAUVAIS  
 Survey Type: CONDITION, SB  
 Sounding Frequency\*\*\*: LOW



0 500 1,000 1,500 2,000 2,500  
 Feet

**NOTES:**  
 Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum: Soundings are shown in feet and indicate depths below Mean Lower Low Water (MLLW, 07-11).  
 Datum Relationships for gage 01625 as of July 2015:  
 0.0' NAVD88 = 0.39' MLLW = 3.89' MLG

Distances on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard.  
 2016 Aerial Photography data source: Precision Aerial Reconnaissance, LLC (1998 DOQQ in green)

Reference is N.O.A.A. Navigation Chart No. 11361.

\*\* Shoal sounding per Quarter per Reach.

\*\*\* High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

Sheet Reference Number  
 9 of 13

Revision Number:  
 4-1-20191105

US Army Corps of Engineers  
 District: CEMVN

Distribution liability: The data represents the results of data collection processing by a specific US Army Corps of Engineers activity and reflects the general existing conditions as such. The user is responsible for the results of any application of the data for other than its intended purpose.

Data Constraints: Hydrographic survey data is subject to change rapidly due to several factors including but not limited to dredging, Army Corps of Engineers actions, and changes in the hydrographic conditions which develop after the date of publication. This data is intended for Army Corps of Engineers use only and is not to be used for any other purpose.

The information depicted on this map represents the results of a survey conducted on the date indicated and can only be considered to be current on the date of condition existing at that time.

|  |                        |
|--|------------------------|
| U.S. ARMY CORPS OF ENGINEERS<br>NEW ORLEANS DISTRICT | Surveyed By: JTB & MGF |
| Submitted: 07/21/2020                                | Printed By: TS         |
| Recommended: Chief Survey Section                    | Checked By: NSK        |
| Approved: Chief Waterways Maintenance Section        |                        |

**MISSISSIPPI RIVER - B.R. TO GULF  
SOUTHWEST PASS - SHEET 9  
SW\_09\_SWP\_20200721\_CS\_PRO**  
 21 July 2020