





LEGEND

--- Federal Navigation Channel

— Federal Navigation Center Line

— As-built Pipeline/Cable

..... Unconfirmed Pipeline/Cable

— Project Depth Contour

○ Cable Area

□ Placement Area

□ Anchorage Area

⊗ Obstruction Point

✶ Wrecks-Submerged

3 Fluff Thickness (feet)*

□ Borrow Area

● Shoalest Sounding**

☆ Beacon, General

◆ Red Navigation Buoy

◆ Green Navigation Buoy

■ -10' and above

■ -10' to -20'

■ -20' to -30'

■ -30' to -40'

■ -40' to -45'

■ -45' to -50'

■ -50' to -55'

■ -55' and below

Gage Reading: CALM

Sea Conditions: BLANCHARD

Vessel Name: CONDITION, SB

Survey Type: LOW

Sounding Frequency***: LOW

1.8 MLLW @ EAST JETTY (01670) @ 1105

Vertical Datum: 0.0' NAVD88, 2009.55 = 0.79' MLLW = 4.29' MLG

Dates on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard.

2024 Aerial Photography data source: Optimal GEO (1998 DOQQ in green)

Reference is N.O.A. Navigation Chart No. 11361.

** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

NOTES:

Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.

Vertical Datum: 0.0' NAVD88, 2009.55 = 0.79' MLLW = 4.29' MLG

Dates on the Mississippi River, above and below Head of Passes are shown at 1 mile intervals.

The location of navigation aids are base on and provided by the U.S. Coast Guard.

2024 Aerial Photography data source: Optimal GEO (1998 DOQQ in green)

Reference is N.O.A. Navigation Chart No. 11361.

** Shoalest Sounding per Quarter per Reach.

*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (24 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

U.S. ARMY CORPS OF ENGINEERS NEW ORLEANS DISTRICT			
Submitted	Surveyed By: LLB & DBD	Plotted By: TSS	Checked By: MSK
Recommended	Chief Survey Section	Chief Survey Section	Chief Survey Section
Approved	Chief Waterways Maintenance Section	Chief Waterways Maintenance Section	Chief Waterways Maintenance Section

MISSISSIPPI RIVER - B.R. TO GULF
SOUTHWEST PASS - SHEET 11
SW_11_SWPX_20251202_CS
02 December 2025

Sheet
Reference
Number
11 of 13

Revision Number:
5.23.12.3-5.23.12.3

US Army Corps
of Engineers
District: CEMVN

DISCLAIMER: The data represented by the results of data collection and processing for a specific US Army Corps of Engineers activity and indicates the general existing conditions. As such, the data is not intended to be used for any purpose other than the intended purpose. The user is responsible for the results of any application of the data for other than the intended purpose. The data is not intended to be used for any purpose other than the intended purpose. The user is responsible for the results of any application of the data for other than the intended purpose.