U.S. ARMY CORPS OF ENGINEERS 3,031,000 458,000 **US Army Corps** of Engineers District: CEMVN 3,028,00**4**58,000 461,000 NOTES: VICINITY MAP Horizontal Coordinate System: North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet. Vermilion Bay **LEGEND** Gage Reading: LELAND BOWMAN: 3.2 MLG AV Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG). Datum Relationships for gage 76720 as of August 2014: 0.0' NAVD88 (OPUS 2014) = 2.08' MLG 1-3 FT. --- Federal Navigation Channel Cable Area Borrow Area Sea Conditions: -8' and above M/V OB189 Vessel Name: _____ -8' and below — Federal Navigation Center Line Placement Area Shoalest Sounding** CONDITION Distances on the Vermilion River are shown at 1 mile intervals. Sounding Frequency***: HIGH Anchorage Area As-built Pipeline/Cable Beacon, General The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE survey crews. Unconfirmed Pipeline/Cable ∅ Obstruction Point Red Navigation Buoy Sheet 2010 Aerial Photography data source: NAIP. Transparent green imagery from 1998 DOQQ. — Project Depth Contour Wrecks-Submerged Reference Reference is N.O.A.A. Navigation Chart No. 11350. Green Navigation Buoy 1,200 Number ** Shoalest Sounding per Quarter per Reach. 17 **of** 49 *** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consoldiated bottom Esri, HERE, DeLorme, MapmyIndia, @ Revison Number: 3.12-20160811 material. Low frequency accuracies may vary depending on channel conditions and fathometer contributors, and the GIS user commu