


Access/Use
The information depicted on this map represents the results of a hydrographic survey conducted in accordance with the standards of the U.S. Army Corps of Engineers. It is not intended for use in any other application. The user is responsible for the accuracy, completeness, and reliability of the data for their intended purpose. The user is responsible for the accuracy, completeness, and reliability of the data for their intended purpose. The user is responsible for the accuracy, completeness, and reliability of the data for their intended purpose.


U.S. ARMY CORPS OF ENGINEERS NEW ORLEANS DISTRICT		
Submitted:	Surveyed By: RYLAND/ADAMS	Plotted By: BD
Recommended:	Chart, Survey Section	Checked By: AC
Approved:	Chart, Waterways Maintenance Section	

**VERMILION RIVER
PERRY**
VM_27_PRY_20170510_CS
10 May 2017



LEGEND

--- Federal Navigation Channel	○ Cable Area	□ Borrow Area	■ -9' and above
— Federal Navigation Center Line	□ Placement Area	● Shoalest Sounding**	□ -9' and below
— As-built Pipeline/Cable	□ Anchorage Area	★ Beacon, General	
..... Unconfirmed Pipeline/Cable	⊗ Obstruction Point	◆ Red Navigation Buoy	
— Project Depth Contour	⚓ Wrecks-Submerged	◆ Green Navigation Buoy	



NOTES:
Horizontal Coordinate System:
North American Datum of 1983 (NAD83), projected to the State Plane Coordinate System (SPCS), Louisiana South Zone. Distance units in U.S. Survey Feet.
Vertical Datum:
Soundings are shown in feet and indicate depths below Mean Low Gulf Datum (MLG).
Datum Relationships for gage 07386980 as of August 2014:
0.0' NAVD83 (OPUS 2014) = 1.96' MLG
Distances on the Vermilion River are shown at 1 mile intervals.
The location of navigation aids are base on and provided by the U.S. Coast Guard and USACE survey crews.
2010 Aerial Photography data source: NAIP. Transparent green imagery from 1998 DOQQ.
Reference is N.O.A. Navigation Chart No. 11350.
** Shoalest Sounding per Quarter per Reach.
*** High frequency (200 kHz) survey data represents the first signal return at a sounding location and will include suspended solids, known as "fluff", if present. Low frequency (20 kHz) survey data normally penetrates through this "fluff" layer to depict elevations of consolidated bottom material. Low frequency accuracies may vary depending on channel conditions and fathometer settings.

Sheet Reference Number
27 of 49

Revision Number:
3.13-20166811